

CHERSON – micro fleece sweatshirt

<p>Description</p>	<ul style="list-style-type: none"> • elasticated collar, waist and cuff, • elongated back bottom to protect the back during bendings, • neck zip 		
<p>Maintenance</p>	<p>Maximum wash temperature: 30°C ; Do not bleach; Do not dry in a tumble dryer; Do not dry clean; Do not iron.</p> 	<p>Item</p>	<p>V553-0-03 Clay brown</p>
		<p>Standards:</p>	
		<p>Sizes</p>	<p>S – 4XL</p>

SAFETY TECHNICAL SPECIFICATIONS

	<i>Test method</i>	<i>Description</i>	<i>Cofra result</i>	<i>Minimum requirement / range</i>
<p>Background fabric</p>	<p>EN ISO 1833-1977, SECTION 10</p>	<p>Composition:</p>	<p>100% polyester</p>	
	<p>EN ISO 12127:1996</p>	<p>Fabric mass per unit area</p>	<p>170 g/m²</p>	
	<p>EN ISO 13688:2013 5.3 (EN ISO 6630 / ISO 5077)</p>	<p>Dimensional change (3N/30°C)</p>	<p>warp: -0.4% weft: -0.3%</p>	<p>±3%</p>
	<p>ISO 105-C06</p>	<p>Colour fastness to Laundering at 40°C</p>		<p>1 - 5</p>
		<p><i>Colour change</i></p>	<p>4-5</p>	
		<p><i>Staining:</i></p>		
		<p>diacetate</p>	<p>4</p>	
		<p>cotton</p>	<p>4-5</p>	
		<p>nylon</p>	<p>4</p>	
		<p>polyester</p>	<p>4-5</p>	
		<p>acrylic</p>	<p>4-5</p>	
		<p>wool</p>	<p>4-5</p>	

	ISO 105 E04	Colour fastness to perspiration <i>Colour change</i> <i>Staining:</i> diacetate cotton nylon polyester acrylic wool	Acidic 4-5 4 4-5 4-5 4-5 4-5 4-5	Alkaline 4-5 4 4-5 4-5 4-5 4-5	1 - 5
	ISO 105-B02	Colour fastness to light	5		1 - 5
	ISO 105-X12	Colour fastness to rubbing	Dry: 4 - 5 Wet: 4 - 5		1 - 5
	ISO 13938-2	Fabric: pneumatic method for determination of bursting strength and bursting distension	607 KPa		>100KPa
CHERSON	ISO 13938-2	Seam: pneumatic method for determination of bursting strength and bursting distension	576 KPa		>100KPa